

Rubber vibration pads: six structures

Start with the contact surface, then confirm dimensions, load and operating conditions.




A-01 Single-Sided Raised-Dot Pad

Product reference photograph



A-02 Double-Sided Raised-Dot Pad

Product reference photograph



B 6x6 Cuttable Raised-Dot Pad

Structure illustration



C-01 Single-Sided Ribbed Pad

Product reference photograph



C-02 Double-Sided Ribbed Pad

Product reference photograph



D Heavy-Duty Deep-Groove Ribbed Pad

Product reference photograph

Common material: synthetic rubber. Typical hardness: 65 ± 5 Shore A. Custom specifications are confirmed by order.

sales@jcxsrubber.com

jcxsrubber.com/rubber-vibration-pads

Dimensions and selection notes

All dimensions in mm: length × width × total thickness, except B and C-02 as noted.

A-01	100×100×16 ; 200×100×16 ; 200×200×16 ; 195×295×20 ; 200×400×16 ; 300×300×16/20/25 ; 400×400×16 ; 600×300×16 ; 600×600×16/20/25 ; 200×200×25
A-02	100×100×16/20 ; 115×115×16/20 ; 200×100×16/20 ; 200×200×16/20/25/30 ; 200×400×16/20 ; 230×230×16/20 ; 230×470×18 ; 300×300×16/20/25/30 ; 400×400×16 ; 600×300×16/20 ; 600×600×16/20/25/30
B	L × W: 100×100 ; 200×100 ; 200×200 ; 300×100 ; 300×200 ; 300×300 ; 400×100 ; 400×200 ; 400×400 ; 500×100 ; 500×200 ; 500×500 ; 600×100 ; 600×200 ; 600×300 ; 600×400 ; 600×600. Thickness references: 15 or 20. Confirm the selected combination and cutting requirement.
C-01	200×400×20 ; 600×600×25/30
C-02	L × W: 200×400 ; 600×600. Common total thickness: 25 or 30. Confirm the selected length, width and thickness combination by order.
D	100×100×20 ; 200×200×20 ; 300×300×30 ; 600×600×30

A slash separates alternative thicknesses, not tolerances. Catalog references do not guarantee stock.

Dimensions, tolerances, samples, minimum order quantity and lead time are confirmed for each request.

For type D, "heavy-duty" describes its deep-groove ribbed structure. Allowable load and vibration-isolation performance require review of the actual installation.

Prepare your quotation request

Copy the items below into an email or website inquiry. Mark any unknown details for review.

01 Model and dimensions

Pad model; length × width × total thickness; holes, cut lines and tolerances.

02 Material and hardness

Required rubber material and Shore A hardness; send an existing sample if specifications are unavailable.

03 Application

Equipment type, installation position, contact footprint and the issue to be addressed.

04 Load and supports

Total equipment weight, number of support points and estimated load per point, if known.

05 Operating environment

Indoor or outdoor use; temperature and exposure to oil, weather or chemicals.

06 Quantity and destination

Trial and production quantities, destination country or port, and requested timing.

07 Drawing or sample

Attach a drawing or photograph and state whether a sample is available for review.

You can inquire with partial information: share what is available so our sales team can clarify the remaining details.
Website attachments: PDF, JPG, PNG, WEBP, DWG or DXF; maximum 8 MB.

sales@jcxsrubber.com

jcxsrubber.com/rubber-vibration-pads